

LESSO



CE
EV Charger

Mobile charge at any time



LSACS-E-32/230-B01
LSACS-E-32/230-B03

Easy switching among multi-gear currents

The default current is 32A, if this current is insufficient for charging at this time, you can adjust the charging current.

Strong compatibility and suitability for various models

Suitable for most new energy vehicle models.

Protection grade: IP66

It has an IP66 waterproof and dust-proof function, and always ensures the charging safety of your car, even in severe outdoor environments.

Technical parameter

Types	LSACS-E-32/230-B01	LSACS-E-32/230-B02	LSACS-E-32/230-B03	LSACS-E-32/230-B04
Output Power	7kW			
Rated Output Voltage	Two-phase 230VAC			
Rated Output Current	32A			
Display Mode	LED light	Display	LED light	Display
Use Method	Swipe card/Bluetooth/Free vend(Optional)		Optional	
Plug Type	Type 2			
Rated Output Frequency	60Hz			
Insulation Resistance	>10MΩ			
Operation Temperature	-20°C~+50°C			
Cable Length	5m (customizable)			
Dimension	Control mainbox: 342 (L) *214(M) *116mm (H)			
Flame Retardant Rating	UL94-V0			
Standard	IEC 62196-1:2022, IEC 61851-1-2017			



LSACS-E-32/230-B02
LSACS-E-32/230-B04

Reservation charging and avoiding peak hours

To take advantage of the cheap price and save on power, you may schedule a charging session for 1~10 hours

8 Safety features

Protection against overheating, overcurrent, leakage, overvoltage, output exception, CP fault, communication fault, and relay fault.

Compressive, strong and durable

The mainbox is made of high-strength PC material with strong, compressive resistance.