

N series

182 N-type Monofacial Module

525W ~ 545W




12 years product
workmanship warranty



25 years linear power output
warranty



1% 1st-year degradation
0.40% annual degradation



FEATURES AND BENEFITS



Topcon technology, higher power generation.



High density packaging, improving energy density.



Better temperature coefficient, more power generation.



Zero LID, increase power generation.



Even cloudy or foggy days, better weak illumination response.



Multiple weather, resistance tests, wider applicability.

LESSO 182 N-type Monofacial Module (66)



Power Range
525W ~ 545W



Power Output Tolerance
0W ~ +5W




Maximum Efficiency
22.95%

(Unit: mm)

Structure Performance

Solar Cell Type	182mm N-TOPCon Mono Cell (Half Cell)
Solar Cell Arrangement	132pcs(6×22)
Module Dimension	2094×1134×30mm
Weight	23.8kg
Front Glass	3.2mm, highly transparent tempered glass with anti-reflective coating
Back Sheet	White
Frame	Anodized Aluminum Alloy
Junction Box	IP68 rated
Cable	4mm ² , portrait 400mm (+) 200mm (-), landscape 1400mm (+) 1400mm (-) Length can be customized
Diode Quantity	3 pcs
Front side / Rear side	5400pa / 2400pa
Connector	MC4 Compatible
Per Pallet	36pcs
Per Container(40'HQ)	792pcs




Electrical Performance Parameters

Model Type		525C(HPM)66(182)		530C(HPM)66(182)		535C(HPM)66(182)		540C(HPM)66(182)		545C(HPM)66(182)	
Testing Condition		STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Nominal Max. Power	P _{MAX} (W)	525	395	530	399	535	403	540	407	545	411
Max. Power Voltage	V _{MPP} (V)	38.83	36.75	38.97	36.92	39.11	37.08	39.24	37.25	39.39	37.42
Max. Power Current	I _{MPP} (A)	13.52	10.75	13.60	10.81	13.68	10.87	13.76	10.93	13.84	10.99
Open Circuit Voltage	V _{OC} (V)	46.31	44.15	46.36	44.29	46.41	44.43	46.46	44.57	46.51	44.71
Short Circuit Current	I _{SC} (A)	14.25	11.56	14.33	11.63	14.41	11.70	14.49	11.77	14.57	11.84
Module Efficiency	(%)	22.11		22.32		22.53		22.74		22.95	

* STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5; NMOT: Irradiance 800W/m², Ambient Temperature 20°C, Air Mass AM1.5, Wind Speed 1m/s; Power measurement tolerance ±3%.

Current-Voltage & Power-Voltage Curve (545C)



Temperature Characteristics

Nominal Module Operating Temperature	44±2°C
Temperature Coefficient (I _{sc})	+0.043%
Temperature Coefficient (V _{oc})	-0.25%
Temperature Coefficient (P _{max})	-0.30%

Maximum Parameters

Working Temperature	-40~+85°C
Maximum System Voltage	1500V DC
Nominal Maximum Fuse Current	25A

