

N series

182 N-type Bifacial Module

575W ~ 595W




12 years product
workmanship warranty



30 years linear power output
warranty



1% 1st-year degradation
0.40% annual degradation



Conventional LESSO Solar Module

FEATURES AND BENEFITS



Topcon technology, higher power generation.



High density packaging, improving energy density.



Even cloudy or foggy days, better weak illumination response.



Zero LID, increase power generation.



Better temperature coefficient, more power generation.



Higher power output, lower bos cost.



Multiple weather, resistance tests, wider applicability.



Double-sided generation, powerfully energy boost.

LESSO 182 N-type Bifacial Module (72)



Power Range
575W ~ 595W




Power Output Tolerance
0W ~ +5W



Maximum Efficiency
23.03%

Structure Performance

Solar Cell Type	182mm N-TOPCon Mono Cell (Half Cell)
Solar Cell Arrangement	144pcs(6×24)
Module Dimension	2278×1134×30mm
Weight	31.2kg
Front Glass	2.0mm, highly transparent tempered glass with anti-reflective coating
Frame	Anodized Aluminum Alloy / Polyurethane Composite Frame
Junction Box	IP68 rated
Cable	4mm ² , portrait ^{400mm (+)} / _{200mm (-)} , landscape ^{1400mm (+)} / _{1400mm (-)} Length can be customized
Diode Quantity	3 pcs
Front side / Rear side	5400pa / 2400pa
Connector	MC4 Compatible
Per Pallet	36pcs
Per Container(40'HQ)	720pcs




Electrical Performance Parameters

Model Type		575C(HBD)72(182)		580C(HBD)72(182)		585C(HBD)72(182)		590C(HBD)72(182)		595C(HBD)72(182)	
Testing Condition		STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Nominal Max. Power	P _{MAX} (W)	575	433	580	437	585	441	590	445	595	449
Max. Power Voltage	V _{MP} (V)	42.60	40.02	42.75	40.17	42.89	40.32	43.04	40.47	43.18	40.62
Max. Power Current	I _{MP} (A)	13.50	10.82	13.57	10.88	13.64	10.94	13.71	11.00	13.78	11.06
Open Circuit Voltage	V _{OC} (V)	51.23	48.66	51.43	48.85	51.63	49.04	51.83	49.23	52.03	49.42
Short Circuit Current	I _{SC} (A)	14.27	11.51	14.33	11.56	14.39	11.61	14.45	11.66	14.51	11.70
Module Efficiency	(%)	22.26		22.45		22.65		22.84		23.03	

* STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5; NMOT: Irradiance 800W/m², Ambient Temperature 20°C, Air Mass AM1.5, Wind Speed 1m/s; Power measurement tolerance ±3%.

Current-Voltage & Power-Voltage Curve (595C)



Bifacial Output-rearside Power Gain

	Maximum Power	P _{MAX} (W)	604	609	614	620	625
	Module Efficiency	(%)	23.37	23.57	23.78	23.98	24.18
5%	Maximum Power	P _{MAX} (W)	633	638	644	649	655
	Module Efficiency	(%)	24.48	24.70	24.91	25.12	25.34
10%	Maximum Power	P _{MAX} (W)	719	725	731	738	744
	Module Efficiency	(%)	27.82	28.07	28.31	28.55	28.79

Temperature Characteristics

Nominal Module Operating Temperature	44±2°C	Temperature Coefficient (V _{OC})	-0.25%
Temperature Coefficient (I _{SC})	+0.043%	Temperature Coefficient (P _{MAX})	-0.30%

Maximum Parameters

Working Temperature	-40 ~ +85°C
Maximum System Voltage	1500V DC
Nominal Maximum Fuse Current	30A