

P series

210 P-type Bifacial Module

595W ~ 605W




12 years product
workmanship warranty



30 years linear power output
warranty



2% 1st-year degradation
0.45% annual degradation



Conventional LESSO Solar Module

FEATURES AND BENEFITS



MBB technology reducing string & busbar loss.



Better temperature coefficient, more power generation.



Even cloudy or foggy days, better weak illumination response.



Zero LID, increase power generation.



High efficiency PERC, better resistance against PID.



Higher power output, lower bos cost.



Multiple weather, resistance tests, wider applicability.



Double-sided generation, powerfully energy boost.

LESSO 210 P-type Bifacial Module (60)



Power Range
595W ~ 605W




Power Output Tolerance
0W ~ +5W



Maximum Efficiency
21.38%

Structure Performance

Solar Cell Type	210mm Mono-crystalline (Half Cell)
Solar Cell Arrangement	120pcs(6×20)
Module Dimension	2172×1303×35mm
Weight	35.6kg
Front Glass	2.0mm, highly transparent tempered glass with anti-reflective coating
Frame	Anodized Aluminum Alloy
Junction Box	IP68 rated
Cable	4mm ² , portrait ^{400mm (+)} / _{200mm (-)} , landscape ^{1400mm (+)} / _{1400mm (-)} Length can be customized
Diode Quantity	3 pcs
Front side / Rear side	5400pa / 2400pa
Connector	MC4 Compatible
Per Pallet	31pcs
Per Container(40'HQ)	558pcs




Electrical Performance Parameters

Model Type	595D(HBD)60(210)		600D(HBD)60(210)		605D(HBD)60(210)	
Testing Condition	STC	NMOT	STC	NMOT	STC	NMOT
Nominal Max. Power P_{MAX} (W)	595	451	600	455	605	459
Max. Power Voltage V_{MP} (V)	34.33	32.01	34.53	32.21	34.73	32.40
Max. Power Current I_{MP} (A)	17.34	14.09	17.38	14.13	17.43	14.17
Open Circuit Voltage V_{OC} (V)	41.60	39.20	41.80	39.40	42.00	39.60
Short Circuit Current I_{SC} (A)	18.33	14.79	18.37	14.83	18.41	14.87
Module Efficiency (%)	21.02		21.20		21.38	

* STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5; NMOT: Irradiance 800W/m², Ambient Temperature 20°C, Air Mass AM1.5, Wind Speed 1m/s; Power measurement tolerance ±3%.

Current-Voltage & Power-Voltage Curve (605D)



Bifacial Output-rearside Power Gain

	Maximum Power P_{MAX} (W)	625	630	635
5%	Module Efficiency (%)	22.08	22.26	22.45
10%	Maximum Power P_{MAX} (W)	655	660	666
	Module Efficiency (%)	23.13	23.32	23.51
25%	Maximum Power P_{MAX} (W)	744	750	756
	Module Efficiency (%)	26.28	26.50	26.72

Temperature Characteristics

Nominal Module Operating Temperature	44±2°C	Temperature Coefficient (V_{OC})	-0.26%
Temperature Coefficient (I_{SC})	+0.048%	Temperature Coefficient (P_{MAX})	-0.34%

Maximum Parameters

Working Temperature	-40~+85°C
Maximum System Voltage	1500V DC
Nominal Maximum Fuse Current	30A

