



Product Service

Attestation of Conformity

No. N8A 116394 0014 Rev. 00

Holder of Certificate: **Guangdong Lesso Banhao
New Energy Technology Group Co., Ltd.**
No. 01, Building 9, Lane 3, East of Dengdong Road,
Longjiang Community, Longjiang Town,
Shunde District,
528318 Foshan City, Guangdong Province
PEOPLE'S REPUBLIC OF CHINA

Product: **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**
[Mono Crystalline Silicon Photovoltaic (PV) Module(s)]

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 64290223141901

Date, 2022-11-22

(Symbol Zhao)

Page 1 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Attestation of Conformity

No. N8A 116394 0014 Rev. 00

Model(s):

555D(HBD)72(182), 550D(HBD)72(182), 545D(HBD)72(182),
540D(HBD)72(182), 535D(HBD)72(182), 530D(HBD)72(182);
510D(HBD)66(182), 505D(HBD)66(182), 500D(HBD)66(182),
495D(HBD)66(182), 490D(HBD)66(182), 485D(HBD)66(182);
465D(HBD)60(182), 460D(HBD)60(182), 455D(HBD)60(182),
450D(HBD)60(182), 445D(HBD)60(182), 440D(HBD)60(182)
420D(HBD)54(182), 415D(HBD)54(182), 410D(HBD)54(182),
405D(HBD)54(182), 400D(HBD)54(182), 395D(HBD)54(182).
670D(HBD)66(210), 665D(HBD)66(210), 660D(HBD)66(210),
655D(HBD)66(210), 650D(HBD)66(210), 645D(HBD)66(210),
640D(HBD)66(210);
610D(HBD)60(210), 605D(HBD)60(210), 600D(HBD)60(210),
595D(HBD)60(210), 590D(HBD)60(210), 585D(HBD)60(210),
580D(HBD)60(210);
550D(HBD)54(210), 545D(HBD)54(210), 540D(HBD)54(210),
535D(HBD)54(210), 530D(HBD)54(210), 525D(HBD)54(210),
520D(HBD)54(210).

Parameters:

Safety class:	Class II
Max. system voltage:	1500 V d.c.
Construction:	Framed, with Junction box, Cable and Connectors

Tested according to:

EN IEC 61730-1:2018
EN IEC 61730-2:2018