

LESSO



EV Charger

Mobile charge at any time





LSACP-16/230-E-A01



LSACP-16/230-E-A02

Easy switching among multi-gear currents

The default current is 10A, if this current is insufficient for charging at this time, you can adjust the charging current.

Strong compatibility and suitability for various models

Suitable for most new energy vehicle models.

Protection grade: IP66

It has an IP66 waterproof and dust-proof function, and always ensures the charging safety of your car, even in severe outdoor environments.

Reservation charging and avoiding peak hours

To take advantage of the cheap price at night and save on power, you may schedule a charging session for 1~10 hours (LSACP-16/230-E-A02 : 1~24hours).

8 Safety features

Protection against overheating, overcurrent, leakage, overvoltage, output exception, CP fault, communication fault, and relay fault.

Compressive, strong and durable

The housing is made of high-strength PC material with strong, compressive resistance.

Technical parameter

Types	LSACP-16/230-E-A01 LSACP-16/230-E-A02
Output Power	3.5kW
Rated Output Voltage	230VAC
Rated Output Current	13A
Display Mode	Standard style: light, Flagship model: 2.4 "color TFT screen
Use Method	Plug and charge
Rated Output Frequency	50Hz
Insulation Resistance	>10MΩ
Operation Temperature	-20°C~+50°C
Line Length	5m (customizable)
Dimension	control box : 200 (L) *90 (M) *55mm (H)
Flame Retardant Rating	UL94-V0
Optional Plug type	European Standard, US Standard, National Standard three-pronged plug, etc