

LESSO

LSBH(50~70)KTL3(-E1)

Three Phase PV Inverter

>> Models:

LSBH50KTL3

LSBH60KTL3

LSBH60KTL3-E1

LSBH70KTL3-E1



Efficient

- Max. efficiency 98.7%
- String current up to 16A
- 5/6 MPPT design, supports multiple orientation system design
- Night time PID recovery function, increases overall system yield (optional)

Smart

- Night SVG function
- Supports export power control
- Intelligent string monitoring, smart I-V curve scan
- Scan to register on Lesso PV cloud, supports remote upgrade and control

Safe

- IP66, C5 Anti-Corrosion Level
- Intelligent redundant fan-cooling
- Globally recognised branded componentry for longer life
- AFCI protection, proactively reduces fire risk

Economic

- Supports GPRS/WiFi communication with less wiring and reduced installation costs
- DC side supports "Y" connector
- Supports aluminium wire access to reduce cost
- 10/12 string inputs allow for 150%+ DC oversizing

DATASHEET

LSBH(50~60)KTL3

LSBH(60~70)KTL3-E1

Models 50K | 60K | 60K-HV | 70K-HV

Input DC

Max. input voltage	1100 V			
Rated voltage	600 V		720 V	
Start-up voltage	195 V			
MPPT voltage range	180-1000 V			
Max. input current	5*32 A		6*32 A	
Max. short circuit current	5*40 A		6*40 A	
MPPT number/Max. input strings number	5/10		6/12	

Output AC

Rated output power	50 kW	60 kW	60 kW	70 kW
Max. apparent output power	55 kVA	66 kVA	66 kVA	77 kVA
Max. output power	55 kW	66 kW	66 kW	77 kW
Rated grid voltage	3L,N,PE, 220 V / 380 V, 230 V / 400 V		3L,PE, 480 V	
Rated grid frequency	50 Hz / 60 Hz			
Rated grid output current	76.0 A / 72.2 A	91.2 A / 86.6 A	72.2 A	84.2 A
Max. output current	83.6 A	100.3 A	79.4 A	92.6 A
Power factor	>0.99 (0.8 leading - 0.8 lagging)			
THDi	<3%			

Efficiency

Max. efficiency	98.7%			
EU efficiency	98.3%		98.4%	

Protection

DC reverse-polarity protection	Yes
Short circuit protection	Yes
Output over current protection	Yes
Surge protection	DC Type II / AC Type II
Grid monitoring	Yes
Anti-islanding protection	Yes
Temperature protection	Yes
Strings monitoring	Yes
I/V Curve scanning	Yes
Integrated AFCI (DC arc-fault circuit protection)	Yes ⁽¹⁾
Integrated PID recovery	Optional ⁽²⁾
Integrated DC switch	Optional

General Data

Dimensions (W*H*D)	691*578*338 mm
Weight	54.5 kg
Topology	Transformerless
Self-consumption (night)	<1 W
Operating ambient temperature range	-25 ~ +60°C
Relative humidity	0-100%
Ingress protection	IP66
Cooling concept	Intelligent redundant fan-cooling
Max. operation altitude	4000 m
Grid connection standard	VDE-AR-N 4105, VDE V 0124, VDE V 0126-1-1, UTE C15-712-1, NRS 097-1-2, G99, EN 50549-1/-2, RD 1699, UNE 206006, UNE 206007-1, IEC61727, DEWA
Safety/EMC standard	IEC 62109-1/-2, IEC62116 & IEC 61000-6-1/-2/-3/-4

Features

DC connection	MC4 connector
AC connection	OT terminal (max. 70 mm ²)
Display	LCD, Capacitive touch buttons
Communication	RS485, USB, Optional: Wi-Fi, GPRS

(1) Activation required. (2) Due to the similar functional logic, when the night time PID-Recovery function is integrated, the night time var compensation function can not be used. Also, the negative grounding option is not available for inverters with night time PID-Recovery function.