

**LESSO**

# Portable Energy Storage



Product Model		P5 Pro	
Battery		LiCoO2 22.2V 499.5Wh	
Input		Fast charging CN: 200V-240V/50HZ, rated input power: 430W US/JP: 100V-120V/60Hz, rated input power: 430W EU/AU/UK: 220V-240V/50Hz, rated input power: 430W	
		Solar panel: MPPT 100W, 18V~24V, 5.6A	
Output	USB-A	MAX 36W 5V3A 9V3A 12V3A support Apple 2.4A, QC2.0/3.0, FCP, AFC, DCP, SCP	
	TYPE-C	MAX 60W 5V3A 9V3A 12V3A 15V3A 20V3A support Apple 2.4A, PPS/PD3.0/PD2.0; QC4+/QC4/QC3.0/QC2.0; AFC; FCP; SCP; PE2.0/PE1.1; SFCP fast charging protocol	
	DC Output	Car Port	12V 10A 120W Max
	AC Output	Sine wave	CN: 220V~240VAC single-phase output, 50Hz, rated output power: 600W US/JP: 100V~120VAC single-phase output, 60Hz, rated output power: 600W EU/AU/UK: 220V~240VAC single-phase output, 50Hz, rated output power: 600W
LED Light		Bright - Off - SOS (3 modes cycle)	
Cycle Life		>1000 times	
Protections		A. over voltage protection B. low voltage protection C. discharge over current protection D. short circuit protection E. charge over current protection F. temperature protection	
Accessories		AC charging line / instruction book	
Dimensions(mm)		251 * 145 * 152	
Weight(kg)		5.1	
Charging Temperature		0~45°C	
Working Temperature		-20~60°C	

Remarks: specifications are subject to change without notice

**Product Specification**



CN



US/JP



EU



AU



UK