



Product Service

# CERTIFICATE

No. Z2 121784 0003 Rev. 00

**Holder of Certificate:** **LESSO New Energy Development Private Limited**

One Raffles Quay, North Tower, #19-03  
Singapore 048583  
SINGAPORE

**Certification Mark:**



**Product:** **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules  
[Mono Crystalline Silicon Photovoltaic (PV) Module(s)]**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 64290223141902B

**Valid until:** 2028-06-08

**Date,** 2023-07-17

( Billy Qiu )

# CERTIFICATE

No. Z2 121784 0003 Rev. 00

## Model(s):

555D(HBD)72(182), 550D(HBD)72(182), 545D(HBD)72(182), 540D(HBD)72(182), 535D(HBD)72(182), 530D(HBD)72(182);  
510D(HBD)66(182), 505D(HBD)66(182), 500D(HBD)66(182), 495D(HBD)66(182), 490D(HBD)66(182), 485D(HBD)66(182);  
465D(HBD)60(182), 460D(HBD)60(182), 455D(HBD)60(182), 450D(HBD)60(182), 445D(HBD)60(182), 440D(HBD)60(182)  
420D(HBD)54(182), 415D(HBD)54(182), 410D(HBD)54(182), 405D(HBD)54(182), 400D(HBD)54(182), 395D(HBD)54(182).  
555C(HBD)72(182), 560C(HBD)72(182), 565C(HBD)72(182), 570C(HBD)72(182), 575C(HBD)72(182), 580C(HBD)72(182), 585C(HBD)72(182);  
510C(HBD)66(182), 515C(HBD)66(182), 520C(HBD)66(182), 525C(HBD)66(182), 530C(HBD)66(182), 535C(HBD)66(182);  
460C(HBD)60(182), 465C(HBD)60(182), 470C(HBD)60(182), 475C(HBD)60(182), 480C(HBD)60(182), 485C(HBD)60(182);  
410C(HBD)54(182), 415C(HBD)54(182), 420C(HBD)54(182), 425C(HBD)54(182), 430C(HBD)54(182), 435C(HBD)54(182).  
670D(HBD)66(210), 665D(HBD)66(210), 660D(HBD)66(210), 655D(HBD)66(210), 650D(HBD)66(210), 645D(HBD)66(210), 640D(HBD)66(210);  
610D(HBD)60(210), 605D(HBD)60(210), 600D(HBD)60(210), 595D(HBD)60(210), 590D(HBD)60(210), 585D(HBD)60(210), 580D(HBD)60(210);  
550D(HBD)54(210), 545D(HBD)54(210), 540D(HBD)54(210), 535D(HBD)54(210), 530D(HBD)54(210), 525D(HBD)54(210), 520D(HBD)54(210).

## Parameters:

Safety class:	Class II
Max. system voltage:	1500 V d.c.
Fire safety class:	Class A or Class C according to UL 790
Construction:	Framed, with Junction box, Cable and Connectors

## Tested according to:

IEC 61215-1:2016  
EN 61215-1:2016  
IEC 61215-1-1:2016  
EN 61215-1-1:2016  
IEC 61215-2:2016  
EN 61215-2:2017  
IEC 61730-1:2016  
EN IEC 61730-1:2018  
IEC 61730-2:2016  
EN IEC 61730-2:2018